



KIP 600 SERIES



SPECIFICATIONS

General

Description	KIP 650 - Color wide format printer KIP 660 - Color wide format print/copy/scan
Type	Electrophotography (LED) with organic photoconductor (OPC) and dry toner system
Range of Productivity	6 D per minute / 360 prints per hour
Warm Up Time	Instant from standby
Rolls	2 Roll
Dimensions	KIP 650 - 59" (w) x 42" (d) x 36" (h) / 1,500 mm x 1,040 mm x 903 mm KIP 660 - 59" (w) x 42" (d) x 42" (h) / 1,500 mm x 1,040 mm x 1,053 mm
Weight	KIP 650 - 715 lb. / 325 kg KIP 660 - 770 lb. / 350 kg
Electrical Requirements	208V-240V +6% -10%, 50/60Hz, 14A
Power Consumption (Standby)	430W
Power Consumption (Printing)	< 1,500W
Power Consumption (Sleep)	3W

Printer

Print Resolution	600 dpi x 2400 dpi
Output Delivery	Top (Front) up to 100 documents based on page size & media type
Roll Capacity	500' Rolls (x2)
Output Sizes Width	11" - 36"
Output Sizes Length	19.7' / 6 m (extendable to 82' / 25 m based on media type)
Media Weights & Types	See KIP Media Guide

Controller

Controller Type	KIP System K Controller
Memory	4GB DDR4 Standard (Upgradable)
Solid State Drive	Minimum 256 GB (Upgradable)
Supported File Type	DWF, PDF, PDF-A, HPGL 1/2, HP-RTL, Calcomp 906/907, CALS Group 4, TIFF Group 4, CIT/TG4, Grayscale TIFF, TIFF Packbits, PNG, JPEG

Scanner

Scanner Type	CIS
Scan Resolution	600 dpi
Scan Format	TIFF, Multipage TIFF, PDF, PDF-A, Multipage PDF, DWF, JPEG
Scan Destination	Local USB (removable media), Mailboxes (local), FTP, SMB Cloud: Google Drive/Dropbox/Box/OneDrive/SharePoint
Original Size Width	11" - 36" / 210 mm to 914 mm
Original Thickness	0.05 mm - 1.60 mm (image quality over 0.25 mm not guaranteed)



For more information on the KIP 600 Series, please contact
Quality Digital Office Solutions at: qualitydos.com/contact